



ENVIROGUARD™[®] ANTIFREEZE/COOLANT

UNIVERSAL HEAVY DUTY PROPYLENE GLYCOL ANTIFREEZE/COOLANT

ENVIROGUARD superior coolant offers very low toxicity in response to PG's favorable safety profile, including the U.S. Food and Drug Administration's GRAS (Generally regarded as safe) rating. Formulated from propylene glycol. It contains an inhibitor package designed to assure anti-foaming properties as well as rust & corrosion protection for brass, copper, solder and aluminum.

PERFORMANCE SPECIFICATIONS

- ASTM D3306
- ASTM D4985
- ASTM D6210
- Caterpillar DEAC
- Chrysler MS7170
- Cummins 90T8-4
- Detroit Diesel 7SE298, 93K217
- EMD M.I. 1748E
- Ford ESE-M97B18-C
- Ford WSS-M97B18-A2
- Freightliner 48-22880
- GM 1825M
- GM 1899M
- GM 6038M
- GSA A-A-52624A
- GSA A-A-870A
- John Deere H24B1, H24C1, H24A1
- Navistar/International B1, Type II (CEMS B-1)
- New Holland WSN-M97D18D
- TMC of ATA RP329/330
- Volvo/Mack
- Waukesha 4-1974D

SPECIFICATIONS:

FREEZING POINT @ 50% -26F
COLOR: **Purple**

PACKAGING OPTIONS

ENVIRO-GUARD™[®] Pre-Charged 100% Concentrate AND 50/50 Pre-diluted

***Product Color: Purple**

275 Gallon Tote

Pack/Unit: 1
Totes Per Truck: 17
Totes Per Truck: 17
Gallons Per Truck: 4675

55 Gallon Drums

Drums per Pallet: 4
Pallets per Truck: 20
Drums per Truck: 80
Gallons per Truck: 4400

Bulk

Gallons per Full Truck Load: 5500
*Partial truck loads can be purchased